PLS225

Loudspeaker cable - 2 x 2.5 mm² - 13 AWG - HighFlex™

Highlights:

- Highflex™ solid & flexible jacket
- 2.5 mm² (13 AWG) thin and dense stranded conductors
- 8 mm (Ø) outer diameter

The PLS225 is a high quality loudspeaker cable consisting of two 2.5 mm² (13 AWG) conductors composed with 224 copper strands of 0.12 mm thickness. The combination of thin and dense strands with high purity copper and the flexible and solid PVC outer jacket makes it the perfect cable for various kinds of applications. The smooth outer jacket provides great ease of installation for fixed systems while having perfect rolling & unrolling performance for highly demanding mobile applications.



Inner Conductors:

STRANDED OXYGEN FREE COPPER

Usage:

Rental

Physical Characteristics:

Inner conductor	Insulation	Material	PVC 3.2 mm (Ø)
		Colours	Red / Blue
Outer jacket	Material		PVC 8 mm (Ø)
	Colours		Black
Type of cable			2-core loudspeaker cable
Inner conductor	Material		BC 224 x 0.12 mm (Ø) (OFC)
	Section		2.5 mm²
	American Wire Gauge		13 AWG
	Number of conductors		2

We reserve the right to change specifications without notice, this is part of our policy to continually improve our products.

Mechanical Characteristics:

Temperature range	Fixed installation	- 20 °C till + 70 °C
	Flexible installation	- 5 °C till + 70 °C
Bending radius	Fixed installation	5 x outer diameter
	Flexible installation	10 x outer diameter

Electrical Characteristics:

Lead resistance	0.8 Ω / 100 m

Cross sections:



We reserve the right to change specifications without notice, this is part of our policy to continually improve our products.